

## IN THE CLAIMS

---

1. (currently amended) A communications system comprising:

a server providing information;

a terminal communicating data with the server;

a communications network connecting said server to said terminal;

a temporary line disconnection unit, provided in the server and the terminal,

monitoring a content of received data from the server and from the terminal, and when a specified data is received, disconnecting a line being used for data communications without issuing any disconnection notifications to an upper layer application of said terminal and said server when said terminal voice communicates with a third party other than said server through said communications network during the data communications with said server, and automatically connecting said server to said terminal when the voice communications terminate;

an automatic data fetch unit automatically fetching data of web sites including information requested by a user from said server to said terminal; and

a storage unit storing the data fetched by said automatic data fetch unit,

wherein a data communicating process is performed from a status at a point immediately before starting the voice communications when said server and said terminal resume the data communications, and

wherein said automatic data fetch unit preliminarily fetches the data obtainable from said server and stores the data in said storage unit during the data communications, and accesses said storage unit during the voice communications so that the data in said storage unit is displayed during the voice communication, thereby realizing virtual data communications during the voice communications.

**2. (original)** The communication system according to claim 1, wherein  
said terminal obtains a telephone number of the third party as information during  
the data communications.

**3. (previously amended)** The communication system according to claim 1,  
wherein

said server comprises a telephone switch unit; and

11  
said temporary line disconnection unit temporarily disconnects a line between  
said server and said terminal when said terminal issue a voice communications request to  
the third party, connecting said telephone switch unit to telephones of the third party and  
said terminal, connecting two calls on a server side, thereby realizing voice  
communications between said terminal and the third party.

**4. (previously amended)** The communications system according to claim 3,  
wherein

said temporary line disconnection unit provided on the server side temporarily  
disconnects the line between said terminal and said server when said terminal issues a  
request for voice communications with the third party to said server; and

said server, a telephone of said third party and said terminal enter a 3-point  
communications state based on a 3-point communication function of said telephone  
switch unit, thereby realizing the voice communications between said terminal and said  
third party.

**5. (previously amended)** The communications system according to claim 1,  
wherein

said temporary line disconnection unit provided on a terminal side temporarily disconnects the line when said terminal issues a request for voice communications with the third party to said server; and

said terminal issues a voice communications call to the third party, thereby realizing the voice communications between said third terminal and said third party.

**6. (previously amended)** The communications system according to claim 1, further comprising

at least one first unit, provided on a server side for each user who receives a service of said server, for managing personal information and communications status of each user, wherein

said temporary line disconnection unit provided on a terminal side temporarily disconnects a line between said terminal and said server according to an instruction from said first unit when said terminal issues a request for voice communications with the third party to said server;

said terminal issues a call through the voice communications to the third party, thereby realizing voice communications between said terminal and said third party,

wherein the server has an object which manages personal information, and the object communicates with an other object which is in said terminal and also manages personal information, before communication by the user, thereby said terminal can receive a call.

**8. (previously amended)** The communication system according to claim 1, further comprising:

a unit for receiving said automatic data fetch unit on a terminal side, wherein

said automatic data fetch unit is transmitted from a server side to the terminal side when the data communications start.

**9. (previously amended)** A communications method comprising the steps of:

(a) connecting a line from a server to a terminal for providing information for data communications with the server through a communications network;

(b) monitoring a content of received data from the server and from the terminal, and when a specified data is received, disconnecting a line being used for data communications without issuing any disconnection notifications to an upper layer application of said terminal and said server when said terminal voice communicates with a third party other than said server through said communications network during the data communications with said server, and automatically connecting said server to said terminal when the voice communications terminate;

(d) automatically fetching data of web sites including information requested by a user from said server; and

(e) storing the data fetched at step (d),

wherein said upper layer applications perform a data communicating process from a status at a point immediately before starting the voice communications when the data communications are resumed,

wherein step (b) is executed in the server and the terminal, and

wherein said steps (d) and (e) are followed during the data communications between said terminal and said server, and said data stored in step (e) is accessed during the voice communications so that said data stored in step (e) is displayed during the voice

communication, thereby establishing virtual data communications during the voice communications.

**10. (original)** The communications method according to claim 9, further comprising the step of:

fetching a telephone number of the third party as information by said terminal during the data communications.

**11. (previously amended)** The communications method according to claim 9, wherein

111  
said step (b) is followed when said terminal issues a voice communications request to the third party, and two calls are connected by a telephone switch unit provided on a server side, thereby realizing voice communications between said terminal and said third party.

**12. (previously amended)** The communications method according to claim 11, wherein

said step (b) is followed on a server side when said terminal issues to said server a request to voice-communicate with the third party;

said server, a telephone of the third party, and said terminal enter a 3-point communications state based on a 3-point communications function of said telephone switch unit, thereby realizing voice communications between said terminal and the third party.

**13. (original)** The communications method according to claim 9, wherein

said step (b) is followed on a terminal side when said terminal issues to said server a request to voice-communicate with the third party;

said terminal issues a call through the voice communications to the third party, thereby realizing voice communications between said terminal and the third party.

**14. (previously amended)** The communication method according to claim 9, further comprising the step of:

(c) managing personal information and communications status on a server side for each user who receives a service from said server, wherein

24/ said terminal issues a call to the third party through the voice communications by following said step (b) based on communications state management in said step (c), thereby establishing voice communications between said terminal and said third party,

wherein the server has an object which manages personal information, and the object communicates with an other object which is in said terminal and also manages personal information, before communication by the user, thereby said terminal can receive a call.

**16. (currently amended)** A server which communicates with a terminal through a communications network, comprising:

a temporary line disconnection unit, monitoring a content of received data from the terminal, and when a specified data is received, disconnecting a line being used for data communications without issuing any disconnection notifications to an upper layer application of the server when said terminal voice communicates with a third party other than the server, when said terminal voice communicates with a third party other than the server through said communications network during the data communications with the server, and automatically connecting the server to the terminal when the voice communications terminate;

an automatic data fetch unit automatically fetching data of web sites including information requested by a user from the server to the terminal; and

wherein a data communicating process is performed from a status at a point immediately before starting the voice communications when the server and the terminal resume the data communications, and

wherein said automatic data fetch unit preliminarily fetches the data obtainable from the server and the server makes the terminal store and display the data, thereby realizing virtual data communications during the voice communications at the terminal side.

14  
17. (previously added) The server according to claim 16, wherein said terminal obtains a telephone number of the third party as information during the data communications.

18. (previously added) The server according to claim 16, further comprising a telephone switch unit; and wherein said temporary line disconnection unit temporarily disconnects a line between said server and said terminal when said terminal issues a voice communications request to the third party, connecting said telephone switch unit to telephones of the third party and said terminal, connecting two calls on a server side, thereby realizing voice communications between said terminal and the third party.

19. (previously added) The server according to claim 18, wherein said temporary line disconnection unit temporarily disconnects the line between said terminal and said server when said terminal issues a request for voice communications with the third party to said server; and

said server, a telephone of said third party, and said terminal enter a 3-point communications state based on a 3-point communications function of said telephone switch unit, thereby realizing the voice communications between said terminal and said third party.

**20. (previously added)** The server according to claim 16, further comprising:

at least one first unit for each user who receives a service of said server, for managing personal information and communications status of each user, wherein said terminal temporarily disconnects a line between said terminal and said server according to an instruction from said first unit when said terminal issues a request for voice communications with the third party to said server;

said terminal issues a call through the voice communications to the third party, thereby realizing voice communications between said terminal and said third party,

wherein the server has an object which manages personal information, and the object communicates with other object which is in said terminal and also manages personal information, before communication by the user, thereby said terminal can receive a call.

**21. (previously added)** The server according to claim 16, wherein said automatic data fetch unit is transmitted from a server side to the terminal side when the data communications start.

**22. (currently amended)** A terminal communicating with a server through a communications network, comprising:

a temporary line disconnection unit, monitoring a content of received data from the server, and when a specified data is received, disconnecting a line being used for data communications without issuing any disconnection notifications to an upper layer



application of the terminal when said terminal voice communicates with a third party other than the server through said communication network during the data communications with the server, and automatically connecting the server to the terminal when the voice communications terminate;

an automatic data fetch unit automatically fetching data of web sites including information requested by a user from the server to the terminal; and

a storage unit storing the data fetched by said automatic data fetch unit,

wherein a data communicating process is performed from a status at a point immediately before starting the voice communications when the server and the terminal resume the data communications, and

wherein said automatic data fetch unit preliminarily fetches the data obtainable from the server and stores the data in said storage unit during the data communications, and accesses said storage unit during the voice communications so that the data in said storage unit is displayed during the voice communication, thereby realizing virtual data communications during the voice communications.

**23. (previously added)** The terminal according to claim 22, wherein said terminal obtains a telephone number of the third party as information during the data communications.

**24. (previously added)** The terminal according to claim 22, wherein said temporary line disconnection unit temporarily disconnects a line between said server and said terminal when said terminal issue a voice communications request to the third party, connecting a telephone switch unit which is provided in the server to telephones of the third party and said terminal, connecting two calls on a server side, thereby realizing voice communications between said terminal and the third party.

**25. (previously added)** The terminal according to claim 24, wherein  
the server temporarily disconnects the line between said terminal and said server  
when said terminal issues a request for voice communications with third party to said  
server; and

said server, a telephone of said third party, and said terminal enter a 3-point  
communications state base on a 3-point communications function of said telephone  
switch unit, thereby realizing the voice communications between said terminal and said  
third party.

**26. (previously added)** The terminal according to claim 22, wherein  
said temporary line disconnection unit temporarily disconnects the line when said  
terminal issues a request for voice communications with the third party to said server; and  
said terminal issues a voice communications call to the third party, thereby  
realizing the voice communications between said terminal and said third party.

**27. (previously added)** The terminal according to claim 22, wherein  
said temporary line disconnection unit temporarily disconnects a line between  
said terminal and said server according to an instruction from a first unit which is  
provided in the server and which manages personal information and communications  
status of each user, when said terminal issues a request for voice communications with  
the third party to said server;

said terminal issues a call through the voice communications to the third party,  
thereby realizing voice communications between said terminal and said third party,

wherein the server has an object which manages personal information, and the  
object communicates with other object which is in said terminal and also manages

personal information, before communication by the user, thereby said terminal can receive a call.

**28. (previously added)** The terminal according to claim 22, further comprising:  
a unit receiving said automatic data fetch unit, wherein  
said automatic data fetch unit is transmitted from a server side to the terminal side  
when the data communications start.

**29. (previously added)** A communication system comprising:  
a server for providing information;  
a terminal for communicating data with the server;  
a communication network for connecting said server to said terminal; and  
temporary line disconnection means, provided in the server and the terminal, for  
disconnecting a line being used for data communications without issuing any  
disconnection notifications to an upper layer application of said terminal and said server  
when said terminal voice-communicates with a third party other than said server through  
said communication network during the data communications with said server, and  
automatically connecting said server to said terminal when the voice communications  
terminate, wherein

a data communicating process is performed from a status at a point immediately  
before starting the voice communications when said server and said terminal resume the  
data communications.

**30. (previously added)** The communication system according to claim 29,  
wherein

said terminal obtains a telephone number of the third party as information during  
the data communications.

31. **(previously added)** The communications system according to claim 29,  
wherein

said server comprises a telephone switch unit; and

said temporary line disconnection unit temporarily disconnects a line between  
said server and said terminal when said terminal issues a voice communications request  
to the third party, connecting said telephone switch unit to telephones of the third party  
and said terminal, connecting two calls on a server side, thereby realizing voice  
communications between said terminal and the third party.

32. **(previously added)** The communications system according to claim 31,  
wherein

said temporary line disconnection unit provided on the server side temporarily  
disconnects the line between said terminal and said server when said terminal issues a  
request for voice communications with the third party to said server; and

said server, a telephone of said third party, and said terminal enter a 3-point  
communications state based on a 3-point communications function of said telephone  
switch unit, thereby realizing the voice communications between said terminal and said  
third party..

33. **(previously added)** The communication system according to claim 29,  
wherein

said line temporary disconnection unit provided on a terminal side temporarily  
disconnects the line when said terminal issues a request for voice communications with  
the third party to said server, and

said terminal issues a voice communications call to he third party, thereby realizing the voice communications between said terminal and said third party.

**34. (previously added)** The communication system according to claim 29, further comprising:

at least one first unit, provided on a server side for each user who receives a service of said server, for managing personal information and communications status of each user, wherein

said temporary line disconnection unit provided on a terminal side temporarily disconnects a line between said terminal and said server according to an instruction from said first unit when said terminal issues a request for voice communications with the third party to said server;

said terminal issues a call through the voice communications to the third party, thereby realizing voice communications between said terminal and said third party,

wherein the server has an object which manages personal information, and the object communicates with an other object which is in said terminal and also manages personal information, before communication by the user, thereby said terminal can receive a call.

**35. (previously added)** The communication system according to claim 29, further comprising:

an automatic data fetch unit automatically fetching data from said server to said terminal; and

a storage unit storing data fetched by said automatic data fetch unit, wherein

said automatic data fetch unit preliminarily fetches data obtainable from said server and stores the data in said storage unit during the data communications, and accesses said storage unit during the voice communications so that the data in said storage unit is displayed during the voice communication, thereby realizing virtual data communications during the voice communications.

**36. (previously added)** The communications system according to claim 29, further comprising:

means for receiving said automatic data fetch unit on a terminal side, wherein said automatic data fetch unit is transmitted from a server side to the terminal side when the data communications start.

**37. (previously added)** A communications method comprising the steps of:

(a) connecting a line from a server to a terminal for providing information for data communications with the server through a communications network; and

(b) disconnecting the line being used for data communications without issuing any disconnection notifications to an upper layer application of said terminal and said server when said terminal voice-communicates with a third party other than said server through said communications network during the data communications with said server, and automatically connecting said server to said terminal when the voice communications terminate, wherein


said upper layer application performs a data communicating process from a status at a point immediately before starting the voice communications when the data communications are resumed.

**38. (previously added)** The communications method according to claim 37, further comprising the step of:

fetching a telephone number of the third party as information by said terminal during the data communications.

**39. (previously added)** The communications method according to claim 37, wherein

said step (b) is followed when said terminal issues a voice communications request to the third party, and two calls are connected by a telephone switch unit provided on a server side, thereby realizing voice communications between said terminal and said third party.

 **40. (previously added)** The communications method according to claim 39, wherein

said step (b) is followed on a server side when said terminal issues to said server a request to voice-communicate with the third party;

said server, a telephone of the third party, and the terminal enter a 3-point communications state base on a 3-point communications function of said telephone switch unit, thereby realizing voice communications between said terminal and the third party.

**41. (previously added)** The communications method according to claim 37, further comprising the step of:

(c) managing personal information and communications status on a server side for each user who receives a service from said server, wherein

said terminal issues a call to the third party through the voice communications by following said step (b) based on communications state management in said step (c), thereby establishing voice communications between said terminal and said third party.

**42. (previously added)** The communications method according to claim 37, further comprising the step of:

(c) managing personal information and communications status on a server side for each user who receives a service from said server, wherein

said terminal issues a call to the third party through the voice communications by following said step (b) based on communications state management in said step (c), thereby establishing voice communications between said terminal and said third party, wherein the server has an object which manages personal information, and the object communicates with an other object which is in said terminal and also manages personal information, before communication by the user, thereby said terminal can receive a call.

**43. (previously added)** The communications method according to claim 37, further comprising the steps of:

(d) automatically fetching data from said server; and

(e) storing data fetched at step (d), wherein

said steps (d) and (e) are followed during the data communications between said terminal and said server; and

said data stored in step (e) is accessed during the voice communications so that said data stored in said step (e) is displayed during the voice communication, thereby establishing virtual data communications during the voice communications.

**44. (previously added)** A server which communicates with a terminal through a communications network, comprising:

a temporary line disconnection unit disconnecting a line being used for data communications without issuing any disconnection notifications to an upper layer application of the server when said terminal voice communicates with a third party other



than the server, when said terminal voice communicates with a third party other than the server through said communication network during the data communications with the server, and automatically connecting the server to the terminal when the voice communications terminate, wherein

a data communicating process is performed from a status at a point immediately before starting the voice communications when the server and the terminal resume the data communications.

**45. (previously added)** The server according to claim 44, wherein said terminal obtains a telephone number of the third party as information during the data communications.

**46. (previously added)** The server according to claim 44, further comprising a telephone switch unit; and wherein said temporary line disconnection unit temporarily disconnects a line between said server and said terminal when said terminal issues a voice communications request to the third party, connecting said telephone switch unit to telephones of the third party and said terminal, connecting two calls on a server side, thereby realizing voice communications between said terminal and the third party.

**47. (previously added)** The server according to claim 46, wherein said temporary line disconnection unit temporarily disconnects the line between said terminal and said server when said terminal issues a request for voice communications with the third party to said server; and

said server, a telephone of said third party, and said terminal enter a 3-point communications state based on a 3-point communications function of said telephone

switch unit, thereby realizing the voice communications between said terminal and said third party.

**48. (previously added)** The server according to claim 44, further comprising:  
at least one first unit for each user who receives a service of said server, for managing personal information and communications status of each user, wherein  
said terminal temporarily disconnects a line between said terminal and said server according to an instruction from said first unit when said terminal issues a request for voice communications with the third party to said server;

said terminal issues a call through the voice communications to the third party, thereby realizing voice communications between said terminal and said third party,

wherein the server has an object which manages personal information, and the object communicates with another object which is in said terminal and also manages personal information, before communication by the user, thereby said terminal can receive a call.

**49. (previously added)** The server according to claim 44, wherein  
said automatic data fetch unit is transmitted from the server side to the terminal side when the data communications start.

**50. (previously added)** A terminal communicating with a server through a communications network, comprising:

a temporary line disconnection unit disconnecting a line being used for data communications without issuing any disconnection notifications to an upper layer application of the terminal when said terminal voice communicates with a third party other than the server through said communications network during the data

communications with the server, and automatically connecting the server to the terminal when the voice communications terminate, wherein

a data communicating process is performed from a status at a point immediately before starting the voice communications when the server and the terminal resume the data communications.

**51. (previously added)** The terminal according to claim 50, wherein said terminal obtains a telephone number of the third party as information during the data communications.

**52. (previously added)** The terminal according to claim 50, wherein said temporary line disconnection unit temporarily disconnects a line between said server and said terminal when said terminal issues a voice communications request to the third party, connecting a telephone switch unit which is provided in the server to telephones of the third party and said terminal, connecting two calls on a server side, thereby realizing voice communications between said terminal and the third party.

**53. (previously added)** The terminal according to claim 52, wherein the server temporarily disconnects the line between said terminal and said server when said terminal issues a request for voice communications with third party to said server; and

said server, a telephone of said third party, and said terminal enter a 3-point communications state based on a 3-point communications function of said telephone switch unit, thereby realizing the voice communications between said terminal and said third party.

**54. (previously added)** The terminal according to claim 50, wherein

said temporary line disconnection unit temporarily disconnects the line when said terminal issues a request for voice communications with the third party to said server; and

said terminal issues a voice communications call to the third party, thereby realizing the voice communications between said terminal and said third party.

**55. (previously added)** The terminal according to claim 50, wherein

said temporary line disconnection unit temporarily disconnects a line between said terminal and said server according to an instruction from a first unit which is provided in the server and which manages personal information and communications status of each user, when said terminal issues a request for voice communications with the third party to said server;

421  
said terminal issues a call through the voice communications to the third party, thereby realizing voice communications between said terminal and said third party,

wherein the server has an object which manages personal information, and the object communicates with another object which is in said terminal and also manages personal information, before communication by the user, thereby said terminal can receive a call.

**56. (previously added)** The terminal according to claim 50, further comprising:

a unit receiving said automatic data fetch unit, wherein

said automatic data fetch unit is transmitted from a server side to the terminal side when the data communications start.

---